ZPTS

Polishing - Gas Conditioning Plant

For Gas liquefaction the required gas quality is more stringent than pipeline quality, in order to produce liquefied methane (LNG), the CO_2 content needs to be under 100ppm . To this end, our **ZPTS® Plant** (Zeolite Pressure Temperature Swing) extracts all carbon dioxide (CO_2) and moisture (H_2O) through molecular sieve adsorption towers. The gas pressure is regulated at the inlet of the CO_2 polishing skidand then enter into a set of modular towers, packed with zeolite that will retain these impurities.

Once saturated, the towers can be regenerated. The ZPTS is designed with enough redundant towers that operation is uninterrupted while other towers are regenerating. This regeneration consists of 3 phases:

- Heating: in this phase desorption occurs, a reverse process to adsorption where the zeolite is heated with high-temperature gas to facilitate the separation of impurities from the zeolites.
- Vacuum: a depressurization and a series of pressure and vacuum pulses are generated that withdrawal these impurities from the towers (which can be used for power generation or other intrinsic user-end processes).
- **Cooling:** finally, the zeolite module is cooled, leaving the tower free from impurities and ready to return to the gas filtering operation.

This regeneration process can be carried out thanks to the presence of two NX-45 compressors integrated into the system and responsible for driving the necessary gas in the closed circuit that makes up each phase mentioned above

Additionally, it should be noted that our Plant presents its mobile version called ZPTS Trailer, which allows the equipment to be easily transported and relocated if required. Its special design with a selftransporting chassis allows the incorporation of carriages for movement and has hydraulic systems to raise it and position it quickly on location.





Process description: **Polishing (zeolite adsorption)**

- **1.** Gas entry into the zeolite tower.
- **2.** Adsorption of H₂O and CO₂ and purified natural gas exits to the liquefaction module.
- **3.** Regeneration of the zeolite bed by heating, vacuum and cooling.





ZPTS

Datasheet

		ZPTS		
Electric Installed Power	KW	304		
	HP	275		
Main Compressors		NX45 (x 2) / MX200 (x1)		
Gas characteristics		Inlet	Outlet	
Pressure (Min/Max)	barg	11 to 16	10 to 15	
	psig	159.5 to 232	145 to 217.5	
Temperature (Min/Max)	°C	10 to 50	30 to 45	
	°F	50 to 122	86 to 113	
Flow (Min/Max)	Sm³/h	900 to 3600	900 to 3600	
	MSCFD	764 to 3056	764 to 3056	
Water	H ₂ O	Saturated	Dry	
Carbon Dioxide	CO ₂	up to 1% @ Max Flow/up to 2% @ Min Flow	< 150 ppm	
Hydrogen Sulfide	H ₂ S	up to 5 ppm		
Nitrogen	N ₂	No limit		
Methane	CH ₄	More than 80%		
Oxygen	O ₂	No limit		
Utilities Consumption	Lube Oil	0.5 L/day (Glygoyle 220 or similar) 0.132 gal/day (Glygoyle 220 or similar)		
	Air	0.6 Nm ³ /h @ 7barg (ISO-8573-1 Type [2;2;2] or higher quality) 0.573 MSCFD @ 101.52psig (ISO-8573-1 Type [2;2;2] or higher quality)		

All values are expressed under a regular operation and may present changes with variation of gas composition and environmental conditions.





ZPTS

Datasheet

Towers	6.6m			
Reg. Module	6.7m			
Towers				
Reg. Module				
Features				
Electrical parameters*				
Main Compressor Start System				
	Towers Reg. Module Towers Reg. Module			

*For lower pressures than 0.8 barg (11.6 psig), a blower skid can be incorporated before the inlet to the unit (optional).. All values are expressed under a regular operation and may present changes with variation of gas composition and environmental conditions.



	ZPTS		
L x 2.4m W x 4.9m H	21.6 ft L x 7.87 ft W x 15.4 ft H		
n L x 2.2m W x 2m H	21.9 ft L x 7.2 ft W x 6.6 ft H		
42 ton	92594 lb		
10 ton	22046 lb		
	Yes		
Yes, 24/7 through our Galileo Global Link Scada System			
	Yes		
Yes			
Yes			
Star-triangle			



Tracked under Galileo Global Link Scada System

We don't just sell technology; we provide a service. We will be with you 24/7, monitoring key parameters through our **Galileo Global Link Scada System*** and providing on-the-ground support to keep your uptime as high as possible.

Up to 99% Methane Recovery, easily tracked through a single integrated system.

Key variables from production, transportation and delivery to end user can be tracked on-line, remotely and in real time in our proprietary SCADA system.

Our integrated solution not only favors efficient troubleshooting and resolution, but it also provides a single control system for the complete operation, from inlet, to gas upgrading, to the outlet of the Virtual Pipeline.

*This is an additional service and is contracted separately.





info@galileoar.com

www.galileoar.com

New Jersey

333 Cedar Ave Middlesex, NJ 08846 United States

Buenos Aires

Av. General Paz Provincia 265 (B1674AOA) Sáenz Peña, Partido de Tres de Febrero Pcia. de Buenos Airees, Argentina



Follow us:



São Paulo Rua Doutor Renato Paes de Barros, 750, Cj. 32, Itaim Bibi, São Paulo, SP, Brasil CEP 04530-001